

# **12** ALL-PURPOSE **ROOF CLEANER**

#### DESCRIPTION

**NC #12 All-Purpose Roof Cleaner** is great for a vast number of applications! Removes soot, pollen, algea, light dirt, mildew. Clean previously coated roofs or prepare roof surfaces for new roof coating applications! NC #12 can also be used on restaurant roofs at grease traps and surrounding areas where grease may be present. Our low viscosity, water-based cleaner breaks down surface inorganics to clean and increase adhesion of roof coatings to the substrate.

#### **APPLICATION**

Apply NC #12 with a 2-3 gallon pressure sprayer at a rate of 300-400 square feet per gallon. *See Dilution Instructions below for your particular application*. Allow the material to stand for 15-20 minutes to wet out and react with the surface. Highpressure rinse the surface with a minimum of 2,000 psi washer, keeping the tip within 12" of the surface. Use a squeegee to push the excess water towards the drains. Surface must be dry before the coating application. The substrate must be coated within 5 days of cleaning.

#### **PREPARATION OF SUBSTRATE**

Remove all visible dirt and debris by broom or air blower prior to application. If concerned about colorfastness, we recommend testing on an inconspicuous area first.

#### **DILUTION INSTRUCTIONS**

GENERAL ROOF CLEANING CLEANER TO WATER: 1:8

Remove pollen, light

dirt, algea, mildew.

Clean coated roofs.



ROOF PREP FOR NEW COATING

Prepare single-ply surfaces for new roof coatings. CLEAN RESTAURANT ROOFS CLEANER TO WATER: 1:4

Clean grease traps & roof surfaces where grease is present. PRESSURE WASH APPLICATIONS CLEANER TO WATER: 1:30

Add cleaner to reservoir of pressure washer & soak surface.



## **QUICK INFO**

#### **TOOLS NEEDED**

Pressure Sprayer Squeegee

SIZES AVAILABLE 1 Gallon Jug

#### **COVERAGE RATE** 300-400 Square Feet per Gallon

### STORAGE PRECAUTION

Do not store close to oxidizers. Keep container closed.

V.O.C. 0 lb/gal (0 g/l)

WARRANTY

This product will perform as claimed if directions are followed. New Castle Building Products cannot control conditions of application and substrate, or methods used. This warranty is limited to replacement of the defective material used, and does not include labor or labor costs.

