

Revision Date: 04.23.25



# 25 MODIFIED LIQUID RUBBER MASTIC

## DESCRIPTION

**NC #25 Modified Liquid Rubber Mastic** is a single-component, thermoplastic rubber mastic formulated for protecting seams, penetrations and other detail areas. NC #25 provides a waterproof, durable, seamless flexible weather resistant membrane with excellent elongation, tensile strength and UV protection.

## USES

**NC #25** is designed for a use on flat or vertical roof surfaces with positive drainage. It may be used on a variety of surfaces including metal, wood, EPDM, APP, TPO and Hypalon.

## APPLICATION

Apply **NC #25** by brush at a rate of 80 linear feet per gallon, according to the substrate and condition. Dry time is 1-6 hours. Cure time is 48 hours. Apply to a clean, dry surface using a brush, roller or squeegee. For best results weather should be clear with no threat of rain for 48 hours.

## COVERAGE

**Metal Surfaces:** Apply at the rate of approximately 1 gallon per 80 linear feet.

**Single-Ply Surfaces:** Apply at the rate of approximately 1 gallon per 80 linear feet.

## PREPARATION OF SUBSTRATE

Surface must be pressure washed clean, free of all loose particles, dirt debris and other contaminants that could inhibit adhesion. Wire brushing may be recommended. The surface must be completely dry to prevent blistering of the product. Must mechanically mix coating before using.

## CLEANUP

Clean tools with citrus cleaner or mineral spirits, taking necessary precautions when handling combustible liquids.

## LIMITATIONS AND PRECAUTIONS

DO NOT THIN. DO NOT HEAT CONTAINER. DO NOT store in an area where temperatures exceed 120°F.



## QUICK INFO

### TOOLS NEEDED

Brush  
Pallet Knife  
Trowel

### COLORS AVAILABLE

White & Black

### SIZES AVAILABLE

3 Gallon Pail

### COVERAGE RATE

1 Gallons per 80 lin. ft.  
(applied in 4" bands)  
400 Screws/Fasteners