



3 ALL-WEATHER FLASHING CEMENT



DESCRIPTION

NC #3 All-Weather Flashing Cement is a high quality cement that is formulated to a heavy smooth trowel consistency. **NC #3 All-Weather Flashing Cement** is a soft pliable material that gradually hardens to a coating that is elastic, durable and resistant to water. Ideal for flashing details and a variety of waterproofing repairs such as roof penetrations and moving joints.

USES

Specially formulated for use in damp, wet roofing situations, **NC #3 All-Weather Flashing Cement** can be used as a heavy duty flashing cement for repairing flashings, asphalt shingles, built-up roofs, metal and masonry surfaces. Great for sealing leaks and openings at flashings (chimneys, vents, skylights, metal joints, gutters). **DO NOT USE** with EPDM, PVC, TPO or other single-ply membranes.

PREPARATION

Surface must be clean and free of dirt, dust, oil or grease and be free of any other foreign matter that would interfere with good adhesion. In colder climates we recommend storing the product at room temperature for 24 hours prior to application.

APPLICATION

Apply with a trowel or putty knife. Spread **NC #3** to approximately 1/8" thickness and work thoroughly into the problem area. Repairing cracks and blisters: if the area is 1/4" wide to 2" long apply cotton or fiberglass fabric for reinforcement, then cover with additional cement.

COVERAGE

Approximately 8 gallons per 100 sq. ft. (per coat)

CLEANUP

Clean tools with a citrus cleaner or mineral spirits, taking necessary precautions when handling combustible liquids.

QUICK INFO

TOOLS NEEDED

Trowel
Spackle/Putty Knife

SIZES AVAILABLE

1 Gallon Pail
5 Gallon Pail

COVERAGE RATE

8 Gallons per
100 sq.ft. (per coat)

CODE APPROVALS/ COMPLIANCE

This product meets or exceeds the requirements of **ASTM 4586 Type I** and **ASTM D-3409**

PRECAUTION

DO NOT THIN. DO NOT HEAT CONTAINER. DO NOT store in an area where temperatures exceed 120°F.

V.O.C. Less than 300 g/L