



8 TROWEL GRADE MODIFIED FLASHING CEMENT



DESCRIPTION

NC #8 Modified Flashing Cement – Trowel Grade is an SBS polymer modified asphalt flashing cement. This product is used on SBS Systems and provides excellent adhesion, as well as a flexible bond on laps and terminations.

USES

NC #8 Modified Flashing Cement – Trowel Grade is primary used for applying SBS modified bitumen membrane flashings to parapet walls, curbs and repairing roof penetrations. Used for sealing laps on SBS modified roofs and also to seal penetrations on APP products. Great for repairing (asphalt shingles, built-up roofs, metal joints, masonry surfaces, chimneys, vents, skylights and gutters) **DO NOT USE** with EPDM, PVC, TPO or other single-ply membranes.

PREPARATION

Surface must be clean and free of dirt, dust, oil or grease and be free of any other foreign matter that would interfere with good adhesion. In colder climates we recommend storing the product at room temperature for 24 hours prior to application.

APPLICATION

Apply with a trowel or putty knife. Spread **NC #8** to approximately 1/8" thickness and work thoroughly into the problem area. Repairing cracks and blisters: if the area is 1/4" wide to 2" long apply cotton or fiberglass fabric for reinforcement then cover with additional cement.

COVERAGE

Approximately 8 gallons per 100 sq. ft. (per coat)

CLEANUP

Clean tools with a citrus cleaner or mineral spirits, taking necessary precautions when handling combustible liquids.

QUICK INFO

TOOLS NEEDED

Trowel
Spackle/Putty Knife

SIZES AVAILABLE

5 Gallon Pail

COVERAGE RATE

8 Gallons per
100 sq.ft. (per coat)

CODE APPROVALS/ COMPLIANCE

This product meets or exceeds the requirements of **ASTM 4586 Type I**